



UNIVERSITY OF KERALA

Thiruvananthapuram, Kerala, India – 695034

(Established as University of Travancore by the Travancore University Act in 1937 and reconstituted as University of Kerala by the Kerala University Act of 1957 and presently governed by the Kerala University Act of 1974 passed by the Kerala State Legislative Assembly)

(Re-accredited by NAAC with A++ Grade)

11906/Ad
A/2026/UOK

BIV
30.07.2026

QUOTATION NOTICE

Competitive Quotations are invited from Vendors within Kerala, for the supply of 3 numbers of computer chairs with following specifications.

Specifications

- 1) Seat/ back assembly : the seat is injection moulded in glass filled polypropylene compound which is upholstered with fabric upholstery covers and moulded polyurethane foam. The back is injection moulded in glass filled polypropylene compound which is upholstered with mesh fabric (refer color chart in product catalog)
seat size : 50.0 cm (W) x 48.0 cm (D)
back size : 53.0 cm (W) x 39.0 cm (H)
- 2) High resilience (Hr) polyurethane foam: The HR polyurethane foam is moulded with density 45 ± 2 kg/m³ and hardness 16 ± 2 kgf as per IS:7888 for 25% compression
- 3) M.S.Powder coated understructure F : The powder coated (DFT 50 ± 10 microns) welded tubular main frame is made from $\varnothing 2.54 \pm 0.03$ cm x 0.2 ± 0.016 cm and $\varnothing 1.9 \pm 0.3$ mm x 0.12 ± 0.0096 mm tube M.S.E.R.W tube
- 4) Armrest: The armrest are made of glass filled polypropylene compound and assembled over the tubular frame.
- 5) Revolving base plate mechanism : The base plate mechanism is 360° revolving type with height adjustment feature.
- 6) Pneumatic Ht. adjustments : The pneumatic seat height adjustment has an stroke of 12.0 ± 0.3 cm
- 7) Pedestal assembly : The pedestal is fabricated from 0.2 ± 0.02 cm thick HR sheet (IS:DD 1079/HR) powder coated (DFT 40-60 microns) and fitted with an injectionable moulded black polypropylene hub cap and 5 nos. twin wheel castors. The pedestal is 60.0 ± 0.5 cm. Pitch-center dia (70.0 ± 1.0 cm with castors)
- 8) Twin wheel castors : The twin wheel castors are injection moulded in black poly amide. Product should have UL greenguards and SCS indoor advantage certificate. OEM should have AIOTA, GRIHA membership certificate.

Conditions

1. The rate quoted should be final, ie, inclusive of GST, transportation charges and any other charges.
2. Complaints with the items supplied should be rectified/replaced to the satisfaction of the University by the suppliers at their own cost.
3. Payment will be made only after the delivery of the item at our site.

Draft #3 oDfate #2 907Ae1 B1906/2026/UOK202607046 Approved by Registrar and 060711-2023 Q614302810924PM - Pa



- Draft #3 oDFile #29057Ac B1906/202B1V012000000K Approved by REGISTRATION - 2023-05-14 2023 09:24:02 - Page 3



RESMI R
Registrar(i/c)

